

Formkuehlung, Zu- und Ruecklaufschlauch G 3/4"
Standort nach Bedarf. Wasserdruck max.6 bar.


Mould cooling, inlet and outlet G 3/4"
position is not fixed. Water pressure max.6 bar's.

Refroidissement du moule, tuyaux flexibles G 3/4"
Eau comprime max.6 bar's.

Kühlwasseranschluß, Ölkühlung
Zulaufrohr R 3/4", Ruecklaufrohr R 3/4", Wasserdruck max. 6 bar

connection for cooling water, oil cooling
Inlet R 3/4", outlet R 3/4", water pressure max. 6 bar

Raccord de l'eau de refroidissement de l'huile
R 3/4" pour l'alimentation et r 3/4" pour l'évacuation.
Eau comprimée maxi 6 bars.



Stromeinspeisung
main power supply
alimentation du courant

Maschinengewicht machine weight poids de presse	6500 kg
Werkzeuggewicht ges. max. total mould weight poids total max. de moule	1485 kg
Hydraulikoel hydraulic oil huile hydraulique	(345 dm ³) ca.302 kg

Das Fundament ist bis auf festen, tragfähigen Grund geführt. Die bauausführende Firma hat die volle Gewähr für die Festigkeit des Fundamentes zu übernehmen.

Alle Maße sind Fertigmaße!

La fondation est à approfondir jusqu'à la couche portante et ferme. L'exécuteur de la fondation doit prendre toutes les garanties sur la solidité de celle-ci.

Toutes les cotes sont des dimensions finies!

The foundation is to be lead on to firm and supporting ground. The contractor has to give full guarantee concerning the stability of foundation.

All measurements are finished sizes!

KM110/125C-SP390/520C
KM110/125C-SP700C

1:20

81
71
61 --> 001170 21.01.99 SVE
51 --> o.Aesi 17.06.98 SVE
41 --> o.Aesi 03.11.97 SVE
31 --> o.Aesi 01.08.97 SVE
21 --> o.Aesi 17.07.97 SVE
11 --> o.Aesi 14.11.96 SVE

1996
21.05. SVE

Fundamentplan
Foundation drawing Plan de fondation

KN121

19B9208X
6484125

6973478.7